

# PRODUCT SHEET

Plastic pull tight seal

## ES 412/L T

<b>Type of seal</b>	pull tight	
<b>Security level</b>	indicative	
<b>Seal body material</b>	PP - Polypropylene	
<b>Seal insert material</b>	steel	
<b>Tension strength</b>	300 N (30 kg)	
<b>Operating temperature</b>	-40°C to +50°C	
<b>Total length</b>	430 mm	
<b>Operating length</b>	300 mm	
<b>Min. size of application hole</b>	8 x 2,5 mm	
<b>Method of application</b>	manual, no tools needed	
<b>Method of removal</b>	manual (tear-off)	
<b>Technology of marking</b>	thermoprinting (standard), hot stamping (optional)	
<b>Marking</b>	Text	YES
	Logo	YES
	Numbering	YES
	Barcode	YES
<b>Remarks to marking</b>	Hot stamping does not allow marking of barcode. Thermoprinting is not suitable for chemically aggressive environments (thinners, solvents, gasoline).	
<b>Colors</b>	yellow, blue	
<b>Packing</b>	10 pcs in mat, 10 mats in PE bag, 2 000 pcs in carton, carton weight 14 kg	
<b>Use</b>	Sealing of cash bags, postal bags, trucks, cistern tank valves, gates, various closures etc.	

