

# PRODUCT SHEET

Plastic pull tight seal

**PL 10/40**

<b>Type of seal</b>	Pull tight	
<b>Security level</b>	indicative	
<b>Seal body material</b>	HDPE - Polyethylene	
<b>Seal insert material</b>	POM - Polyoxymethylen	
<b>Tension strength</b>	100 N (10 kg)	
<b>Operating temperature</b>	-40°C to +50°C	
<b>Total length</b>	400 mm	
<b>Operating length</b>	300 mm	
<b>Min. diameter of application hole</b>	4 mm	
<b>Method of application</b>	manual, no tools needed	
<b>Method of removal</b>	light cutting tool	
<b>Technology of marking</b>	Thermoprinting (standard), hot stamping (optional)	
<b>Marking</b>	Text	Print field 40 x 18 mm (thermoprinting)
	Logo	YES
	Numbering	YES
	Bar code	YES
<b>Remarks to marking</b>	Marking possibility with hot stamping – text in two lines (2 x 8 characters) and numbering with 6 digits. Marking of bar code only with thermoprinting, double sided printing available. Ideal logo resolution for production 300 dpi, formats jpg, ai, eps, bmp, gif.	
<b>Colors</b>	white, yellow, red, blue, green	
<b>Packing</b>	10 pcs in mat, 10 mats in PE bag, 2 000 pcs in carton, carton weight 11 kg	
<b>Use</b>	Money and cash bags, tank valves, lockers, trucks, rails cars etc.	

