



PRODUCT SHEET

Plastic seal Eurolock

PL 2006/12

| | | |
|--|--|--|
| Type of seal | Eurolock | |
| Security level | indicative | |
| Seal body material | HDPE - Polyethylene | |
| Seal insert material | POM - Polyoxymethylen | |
| Tension strength | 80 N (8 kg) | |
| Operating temperature | -40°C to +50°C | |
| Total length | 122 mm | |
| Operating length | 79 mm | |
| Min. diameter of application hole | 4 mm | |
| Method of application | manual, no tools needed | |
| Method of removal | manual, no tools needed | |
| Technology of marking | hot stamping, laser engraving | |
| Marking | Text | 2 lines, 6 characters, (2 x 6) |
| | Logo | YES |
| | Numbering | 6 or 7 digits, 1 character + 6 digits or 2+5 |
| | Bar code | YES |
| Remarks to marking | Laser engraving enables higher number of digits and characters also in combination with logo. Laser engraving is suitable only for light colors of seals. Hot stamping allows printing of text or logo only. | |
| Colors | yellow, red, green, blue | |
| Packing | 10 pcs in bunch, 10 bunches in PE bag, 5 000 pcs in carton, carton weight 12,5 kg | |
| Use | Sealing of different closures, cabinets, luggage etc. | |

