

# PRODUCT SHEET

Plastic pull tight seal

**PL 91/32**

<b>Type of seal</b>	Pull tight	
<b>Security level</b>	indicative	
<b>Seal body material</b>	HDPE - Polyethylene	
<b>Seal insert material</b>	POM - Polyoxymethylen	
<b>Tension strength</b>	100 N (10 kg)	
<b>Operating temperature</b>	-40°C to +50°C	
<b>Total length</b>	320 mm	
<b>Operating length</b>	243 mm	
<b>Min. diameter of application hole</b>	4 mm	
<b>Method of application</b>	manual, no tools needed	
<b>Method of removal</b>	manual/light cutting tool	
<b>Technology of marking</b>	Hot stamping, laser engraving, inkjet printing	
<b>Marking</b>	Text	2 lines, 8 characters, (2 x 8)
	Logo	YES
	Numbering	6 or 7 digits, 1 character + 6 digits or 2+5
	Bar code	YES
<b>Remarks to marking</b>	Laser engraving enables higher number of digits and characters also in combination with logo. Laser engraving is suitable only for light colors of seals. Hot stamping allows printing of text or logo only.	
<b>Colors</b>	white, yellow, orange, red, blue, green, brown, grey, black	
<b>Packing</b>	10 pcs in bunch, 10 bunches in PE bag, 2 000 pcs in carton, carton weight 8,40 kg	
<b>Use</b>	Money and cash bags, tank valves, cabinets, lockers, various closures etc.	

