

# PRODUCT SHEET

Plastic seal Eurolock

**PL 95/12W**

<b>Type of seal</b>	Eurolock	
<b>Security level</b>	indicative	
<b>Seal body material</b>	HDPE - Polyethylene	
<b>Seal insert material</b>	POM - Polyoxymethylen	
<b>Tension strength against insert</b>	150 N (15 kg)	
<b>Operating temperature</b>	-40°C to +50°C	
<b>Total length</b>	123 mm	
<b>Operating length</b>	5 mm	
<b>Min. diameter of application hole</b>	4 mm	
<b>Condition of use</b>	plastic clamp for seal PL 95/12W	
<b>Method of application</b>	manual, no tools needed	
<b>Method of removal</b>	cutting tool	
<b>Technology of marking</b>	hot stamping, laser engraving	
<b>Marking</b>	Text	2 lines, 6 characters, (2 x 6)
	Logo	YES
	Numbering	6 or 7 digits, 1 character + 6 digits or 2+5
	Bar code	YES
<b>Remarks to marking</b>	Laser engraving enables higher number of digits and characters also in combination with logo. Laser engraving is suitable only for light colors of seals. Hot stamping allows printing of text or logo only.	
<b>Colors</b>	white, yellow, red, blue, green	
<b>Packing</b>	10 pcs in bunch, 10 bunches in PE bag, 4 000 pcs in carton, carton weight 10 kg	
<b>Use</b>	Sealing of gas and water meters.	

